



PERFORMANCE RANGE

- Flow rate up to **120 l/min** (7.2 m³/h)
- Head up to **105 m**

APPLICATION LIMITS

- Maximum liquid temperature **+40 °C**
- Maximum sand content **50 g/m³**
- **20 m** maximum immersion depth
- Continuous service **S1**

CONSTRUCTION AND SAFETY STANDARDS

Complete with **20 m** long power cable

EN 60335-1
IEC 60335-1
CEI 61-150

EN 60034-1
IEC 60034-1
CEI 2-3



CERTIFICATIONS



AN30

INSTALLATION AND USE

As a result of their high efficiency and reliability they are suitable for use with clean water in domestic, civil and agricultural applications such as the distribution of water in combination with pressure sets, for the irrigation of gardens and allotments and for pressure boosting, etc.

OPTIONALS AVAILABLE ON REQUEST


- Pumps fitted with power cables of other lengths
- Other voltages or 60 Hz frequency

GUARANTEE

1 year subject to terms and conditions

CHARACTERISTIC CURVES AND PERFORMANCE DATA

50 Hz n = 2900 1/min



VERSION WITHOUT FLOAT SWITCH

MODEL		POWER		Q	m³/h l/min	0	0.6	1.2	1.8	2.4	3.0	3.6	4.2	4.8	5.4	6.0	6.6	7.2
Single-phase	Three-phase	kW	HP			0	10	20	30	40	50	60	70	80	90	100	110	120
NKm 2/1	–	0.45	0.6	H metres	36	35	33	31	28.5	26	23	19	15					
NKm 2/2	–	0.55	0.75		48	46	44	41.5	39	35	30	25	19					
NKm 2/3	NK 2/3	0.75	1		60	58	55	51	47	42	36	30	23					
NKm 2/4	NK 2/4	1.1	1.5		84	80	75	70	65	59	51	42.5	34					
NKm 2/5	NK 2/5	1.5	2		90	87	83	78	73	66	58	48	38					
NKm 4/1	–	0.55	0.75		40	–	37	36	34.5	32.5	30	28	25	21.5	18.5	14.5	10	
NKm 4/2	NK 4/2	0.75	1		50	–	48	46	44	41	38	35	32	28	24	19	14	
NKm 4/3	NK 4/3	1.1	1.5		67	–	65	62.5	60	56.5	52	48	44	38	32	25	18	
NKm 4/4	NK 4/4	1.5	2		75	–	72	69	66	64	60	57	53	48	43	38	32	
NKm 4/5	NK 4/5	2.2	3		105	–	101	98	94	90	86	80	75	67	60	52	44	

"GE" VERSION WITH FLOAT SWITCH


MODEL	POWER		Q	m³/h	0	0.6	1.2	1.8	2.4	3.0	3.6	4.2	4.8	5.4	6.0	6.6	7.2	
	kW	HP			l/min	0	10	20	30	40	50	60	70	80	90	100	110	120
Single-phase			H metres															
NKm 2/1 - GE	0.45	0.6			36	35	33	31	28.5	26	23	19	15					
NKm 2/2 - GE	0.55	0.75			48	46	44	41.5	39	35	30	25	19					
NKm 2/3 - GE	0.75	1			60	58	55	51	47	42	36	30	23					
NKm 2/4 - GE	1.1	1.5			84	80	75	70	65	59	51	42.5	34					
NKm 2/5 - GE	1.5	2			90	87	83	78	73	66	58	48	38					
NKm 4/1 - GE	0.55	0.75			40	–	37	36	34.5	32.5	30	28	25	21.5	18.5	14.5	10	
NKm 4/2 - GE	0.75	1			50	–	48	46	44	41	38	35	32	28	24	19	14	
NKm 4/3 - GE	1.1	1.5			67	–	65	62.5	60	56.5	52	48	44	38	32	25	18	
NKm 4/4 - GE	1.5	2			75	–	72	69	66	64	60	57	53	48	43	38	32	
NKm 4/5 - GE	2.2	3		105	–	101	98	94	90	86	80	75	67	60	52	44		

Q = Flow rate H = Total manometric head

Tolerance of characteristic curves in compliance with EN ISO 9906 App. A.


POS.	COMPONENT	CONSTRUCTION CHARACTERISTICS				
1	EXTERNAL SLEEVE	Stainless steel AISI 304, complete with threaded delivery port in compliance with ISO 228/1				
2	SUCTION FILTER	Stainless steel AISI 304				
3	MOTOR SLEEVE	Stainless steel AISI 304				
4	IMPELLERS AND DIFFUSERS	Noryl GFN2V				
5	DIAPHRAGMS	Stainless steel AISI 304, complete with anti-wear ring				
6	MOTOR SHAFT	Stainless steel EN 10088-3 - 1.4104				
7	TWO MECHANICAL SEALS SEPARATED BY AN OIL CHAMBER					
	<i>Seal</i>	<i>Shaft</i>	<i>Position</i>	<i>Materials</i>		
	<i>Model</i>	<i>Diameter</i>		<i>Stationary ring</i>	<i>Rotational ring</i>	<i>Elastomer</i>
	MG1-16	Ø 16 mm	Motor side	Silicon carbide	Graphite	NBR
	MG1-15 SIC	Ø 15 mm	Pump side	Silicon carbide	Silicon carbide	NBR
8	BEARINGS	6303 2RS - C3 / 6203 ZZ - C3				
9	CAPACITOR					
	<i>Pump</i>	<i>Capacitance</i>				
	<i>Single-phase</i>	<i>(230 V or 240 V)</i>		<i>(110 V)</i>		
	NKm 2/1	16 µF 500 VL	30 µF 250 VL			
	NKm 2/2	16 µF 500 VL	30 µF 250 VL			
	NKm 4/1	16 µF 500 VL	30 µF 250 VL			
	NKm 2/3	20 µF 500 VL	–			
	NKm 4/2	20 µF 500 VL	–			
	NKm 2/4	25 µF 500 VL	–			
	NKm 4/3	25 µF 500 VL	–			
10	ELECTRIC MOTOR					
	NKm: single-phase 230 V - 50 Hz with thermal overload protector built-in to the winding.					
	NK: three-phase 400 V - 50 Hz.					
	– Insulation: F class.					
	– Protection: IP 68.					
11	POWER CABLE					
	➡ 20 metre long DRINCABLE® for permanent immersion in drinking water					
12	FLOAT SWITCH					

The diagram illustrates the internal components of a submersible pump assembly. The components are numbered as follows: 1. External sleeve at the top; 2. Suction filter below the sleeve; 3. Motor sleeve surrounding the motor; 4. Impellers and diffusers in the center; 5. Diaphragms separating the motor and pump chambers; 6. Motor shaft passing through the diaphragms; 7. Two mechanical seals on the shaft, separated by an oil chamber; 8. Bearings supporting the shaft; 9. Capacitor connected to the motor; 10. Electric motor winding; 11. Power cable entering the top; 12. Float switch at the bottom.



DIMENSIONS AND WEIGHT

MODEL		PORT DN	N° STAGES	DIMENSIONS mm		kg	
Single-phase	Three-phase			Ø	h	1~	3~
NKm 2/1	–	1 1/4"	3	135	495	13.9	–
NKm 2/2	–		4		519	14.5	–
NKm 2/3	–		5		573	16.3	–
–	NK 2/3				543	–	15.0
NKm 2/4	NK 2/4		7		621	18.1	18.0
NKm 4/1	–		4		519	14.3	–
NKm 4/2	–		5		573	16.2	–
–	NK 4/2				543	–	15.1
NKm 4/3	NK 4/3		7		621	18.1	18.0



ABSORPTION

MODEL	VOLTAGE (single-phase)		
Single-phase	230 V	240 V	110 V
NKm 2/1	4.5 A	4.5 A	9.0 A
NKm 2/2	5.0 A	5.0 A	10.0 A
NKm 2/3	6.0 A	6.0 A	–
NKm 2/4	7.5 A	7.5 A	–
NKm 4/1	5.0 A	5.0 A	10.0 A
NKm 4/2	6.0 A	6.0 A	–
NKm 4/3	7.5 A	7.5 A	–

MODEL	VOLTAGE (three-phase)			
Three-phase	230 V	400 V	240 V	415 V
NK 2/3	4.5 A	2.6 A	4.5 A	2.6 A
NK 2/4	5.2 A	3.0 A	5.2 A	3.0 A
NK 4/2	4.5 A	2.6 A	4.5 A	2.6 A
NK 4/3	5.2 A	3.0 A	5.2 A	3.0 A

PALLETIZATION

MODEL		GROUPAGE			CONTAINER			
Single-phase	Three-phase	n° pumps	H (mm)	kg 1~ 3~	n° pumps	H (mm)	kg 1~ 3~	
NKm 2/1	–	30	1015	434 –	60	1890	852 –	
NKm 2/2	–	30	1015	452 –	60	1890	887 –	
NKm 4/1	–							
NKm 2/3	–	25	869	425 –	40	1307	670 –	
NKm 4/2	–							
–	NK 2/3 NK 4/2	30	1015	– 470	60	1890	– 915	
NKm 2/4	NK 2/4	25	869	469 467	40	1307	740 737	
NKm 4/3	NK 4/3							

